

A world leader in high tech mobile spray application equipment





Ramp Unit De-icers



Zero Velocity Spreaders



Truck Mounted De-icers



Trailer Mounted De-icers



Slide-in Units

Wausau Equipment Company, Inc. 1905 South Moorland Road New Berlin, WI 53151-2321

800-788-6066 - 262-784-6066 262-784-6720 - fax www.wausau-everest.com















819-838-5653 - fax www.wausau-everest.com

CANADA

Wausau-Everest L.P. reserves the right to change products and specifications without notice. Visit us at www.wausau-everest.com

WAUSAU • EVEREST

819-838-4257

Ayer's Cliff, Quebec J0B 1C0

Everest Equipment Co. 1077 Westmount



Airport De-icer

Truck Mounted



50, 75 or 100 Ft. boom width 250 gallon - 5000 gallon tank capacity

Pump Station

- •9, 16 or 18 HP engine packages available.
- •300 GPM centrifugal pump •Integral pump station
- capable of load, unload and transfer

Power Boom Folds

 Available with full cab controlled power or manual booms

3-Section Boom Shut-off

•Capable of spraying in the fully closed position which allows roadway applications

Heavy Duty Trailer

- •Low center of gravity
- •Power Surge brakes

Trailer Mounted



10 Ft. - 50 Ft. boom width
250 gallon - 3000 gallon tank capacity, stainless steel or poly
Available with cab controlled engine and spray functions

Tyler GETM CONTROL

5-Section Boom Shut-off

Booms may be sprayed in fully closed position, partially opened position, or fully opened position. Boom widths of 50', 75' or 100' available.

Spray Boom

Strongest spray boom in the industry. Constructed of rectangular tubing, and equipped with breakaway features for each wing. When in the cradle position, the tips fold back behind the cab door, so no need to walk under dripping chemical when entering and leaving the cab.

The Spray Boom

Features:



Spray Pattern / Nozzle Selection System

No need to remove nozzle when changing from light to heavy application, or when changing from de-icing to anti-icing operations. The unique Tyler "Select A Spray" design allows for complete change over in less than 1 minute. No need to stock additional nozzles, extensions, screens, etc. for various configurations. Stop over-spraying expensive chemicals with the blast button. Apply accurately with the Tyler Ice System. Built-in spring flush check valve. Pull the lever to clear any debris from your check valve. Tyler, ready when you need to go.



Control Console

The convenient control console features pre-set application rates. Easy operator control does not require extensive training to operate. The auto start and stop eliminates the need to hold "blast".

Driver's Side Pumping Station

Valving and pumping station is conveniently located near the driver's side door. No need to reach between the spray boom when loading and setting up valving. Each valve handle is color coded for easy understanding of all operations. Load line located low, eliminating potential splashing of materials into the operator's face during hookup and disconnection.

