

UTS-9
**UNDER TAILGATE
SPREADER**

**WE'VE GOT YOU
COVERED**



THE ONLY UNDER TAILGATE SPREADER with a FOLD FLAT COVER/BACKPLATE
Easiest to clean. Easiest to maintain.

Sourcewell 
Awarded Contract
Contract # 080818-HEN

HENKE 
AN ALAMO GROUP COMPANY



THE ULTIMATE CHOICE FOR EASY MAINTENANCE AND SUPERIOR PERFORMANCE



Check out our product demo video on YouTube

A DEDICATED TEAM THAT DELIVERS

Listening to our customers helps us understand the unique challenges they're faced with. That, in turn, helps our engineering and manufacturing team use their expertise to design solutions that perform beyond specs and expectations.

When you call on HENKE, you'll receive first rate service backed by a team of seasoned industry professionals. With HENKE, **your** concern is **our** concern and we do everything we can to create a successful outcome for you.

HENKE'S HXC Cartridge Spreader, The only V-Box Spreader on the market with a removable conveyor system, designed to be easy to maintain and cost-effective for the long haul.

Learn more about it in our YouTube video



AN ALAMO GROUP COMPANY

888.682.9010
henkemfg.com



UNIQUE MULTI-POSITION COVER/BACKPLATE

Henke's UTS-9 features 4 different settings from fully closed to fully open in a 90° flat position. This gives you the easiest position to clean and maintain the 9" auger and spreader unit.



SET-BACK POSITION FOR INCREASED MATERIAL CAPACITY

Opening the spreader to the set-back position allows for additional tailgate swing giving you increased material capacity.



SAFETY LOCK-OUT DEVICE

Safety is important at Henke Manufacturing, the UTS-9 is designed to disengage the motor when gaining access to the auger. Additionally, our exclusive side mounting plates limit access during operation.



BETTER MATERIAL FLOW BY DESIGN

Our sloped rear apron helps shed material from the dump body into the conveyor trough and helps prevent material build-up. This increases your operating uptime and decreases needed cleaning.



DESIGNED TO BE EASY TO MAINTAIN AND PREVENT DOWNTIME

The offset motor mount makes maintenance a snap while preventing material build-up on the shaft which can prematurely blow a seal.



FOLD FORWARD CLEAN OUT

The first step in using the fold forward clean out is to disengage the safety lock-out device. The spinner assembly stays attached giving you quick and easy access.



ALL-SEASON USE

The optional berm chute gives you the flexibility to disperse aggregate.

SPECIFICATIONS
Body is designed to fit below the dump bodies tailgat with outside widths ranging from 94" - 96" Unit overall width: 96" Approximate weight: 66lbs
Heavy-duty 70gauge cover/backplate and trough with 1/4" endgates
9" diameter carbon steel auger. Auger shaft is tapped at one end to allow installation of speed sensor
3 heavy-duty latches keep cleanout door securely sealed
20" polyurethane spinner disk is adjustable front-to-back and side-to-side and can be removed without tools
Auger motor is offset from hopper body to prevent damage to seal
Quick disconnect mounting kit with 1/4" pins