

ULTI-MATE "HANDS FREE" HITCH

• WAUSAU[™] Ulti-Mate Hitch allows hands-free interchange of the plow and other attachments.

ULTI-MATE HITCH

KEEPING AHEAD OF THE CUTTING EDGE™

- The Ulti-Mate Hitch is hydraulically operated (plow lift, swing, and lock) and designed for power reversible runway plows.
- The entire process of hitching or unhitching is possible in less than 2 minutes, by one person, and is connected with hydraulically operated lock pins.



FEATURES:

- Construction: Welded tubular and plate steel.
- Two (2) 360° swivel adjustable, pneumatic, dual caster wheel assemblies
- Hitch: Parallel lifting type consisting of two (2) parallel tubular push arms of 3" x3" x 5/16" wall steel tubing so when the plow is carried in the raised position, and angled right or left, it remains level to the pavement
- Hydraulic double-acting-lift cylinder, 4" bore x 16-3/8"stroke, with a 2" diameter rod
- Four (4) heavy-duty braces on top of the frame, which can adjust the cutting edge angle to positions of 65°, 75°, and 85°

WAUSAU

- A mechanical transport lock takes the weight of the plow off the hydraulic cylinder during transport, and acts as a safety in the event of a hose failure during transport
- Once detached, the mold board and push frame will rest on the ground, caster tires, and the cutting edge only
- No blocking is needed

Wausau Equipment Company, Inc. 1905 South Moorland Road New Berlin, WI 53151-2321 U.S.A.

800-788-6066 ~ 262-784-6066 262-784-6720 - fax

ISO 9001:2000 Certified

WAUSAU • EVEREST

HEAVY-DUTY SNOW & ICE CONTROL

Everest Equipment Company 1077 Westmount Ayer's Cliff, Quebec J0B 1C0 CANADA

819-838-4257 819-838-5653 – fax

Wausau-Everest L.P. reserves the right to change products and specifications without notice. Visit us at www.wausau-everest.com