SNOWPLOWS





OFTEN IMITATED - NEVER EQUALED - HomeSafe

HOMESAFE POLY SERIES





HOMESAFE POLY HOTWING SERIES



HOMESAFE STEEL SERIES





This is the most popular plow on the market for a reason. When it comes to a plow that can handle tough and varying terrains, this plow will get you home... safe.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
HSP3610	10′	8′	36"	3/8"	2100
HSP3611	11′	8′ 9″	36"	3/8"	2180
HSP4210	10′	8′	42"	3/8"	2260
HSP4211	11′	8' 9"	42"	3/8"	2340
HSP4212	12′	9′ 6″	42"	3/8"	2420
HSP4214	14′	11'4"	42"	3/8"	2540
HSP4811	11″	8' 9"	48"	3/8"	2500
HSP4812	12′	9′6″	48″	3/8"	2580

Choose between hydraulic or manual reversing. Available options also include: single or dual mailbox cuts, rubber or poly snow deflectors, air foils, snow wheels

Choose the HotWing HomeSafe Plow for superior discharge and ability to cast and throw snow.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT AT CENTER	HEIGHT AT DISCHARGE	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
HSP4211HW	11′	8′ 9″	42"	54 1/2"	3/8"	2440
HSP4212HW	12′	9'6"	42"	57″	3/8"	2520
HSP4811HW	11′	8′ 9″	48"	60"	3/8"	2600
HSP4812HW	12′	9'6"	48″	62"	3/8"	2680
HSP5611HW	11′	8′ 9″	56″	70"	3/8"	2820
HSP5612HW	12′	9′6″	56″	72″	3/8"	2900

Choose between hydraulic or manual reversing. Available options also include: rubber or poly snow deflectors, air foils, snow wheels

Wausau offers a steel moldboard version of the HomeSafe design.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
HSS3610	10′	8′	36″	3/16″	2205
HSS3611	11′	8' 9"	36″	3/16″	2285
HSS4210	10′	8′	42"	3/16"	2365
HSS4211	11′	8′ 9″	42"	3/16"	2445
HSS4212	12′	9' 6"	42"	3/16"	2525
HSS4214	14′	11′4″	42"	3/16"	2640

Choose between hydraulic or manual reversing. Available options also include: single or dual mailbox cuts, rubber or poly snow deflectors, air foils, snow wheels

*Note: all weights listed are a minimum based on a standard unit

OFTEN IMITATED - NEVER EQUALED - HomeSafe

HOMESAFE ONE-WAY





When it comes time to throw and cast snow out of the way, Wausau's HomeSafe One-Way Plow is the answer. Our heavy-duty smooth rolled moldboard with solid welded ribs will stand up to years of hard use. The overhang design is great for driver visibility and eliminating annoying over-spray. Wausau's trip mechanism consists of 3/4" square wire horizontal torsion springs.

MODEL	LENGTH CUTTING EDGE (ft)	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	TRIP SPRINGS	WEIGHT (lbs)*
HSS2656	11′	12′8"	9′ 0"	26"	56″	10ga	5 Torsion	2360
HSS2658	12′	12' 8"	9' 8"	26″	58″	10ga	6 Torsion	2460

Available options also include: rubber or poly snow deflectors, air foils, snow wheels, sight markers, carbide cutting edges, curb guards etc.

*Note: all weights listed are a minimum based on a standard unit



MF Street Smart - MULTI-SECTION PLOW





The Street Smart[™] plow is a multi-section, shock absorbing, reversible snowplow. Each section functions independently to enhance snow removal operation for all types of conditions. Designed for added safety to protect plow, hitch, truck, and operator. Adapts to all types of hitches.

MODEL	LENGTH CUTTING EDGE (ft)	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	TRIP SPRINGS	WEIGHT (lbs)*
MF3.4	11′	12′8"	9′ 0"	26"	56″	10ga	5 Torsion	2360
MF5.4	12′	12' 8"	9' 8"	26″	58″	10ga	6 Torsion	2460

When the Street Smart[™] plow hits an obstacle, the flexible shock rail absorbs the impact and springs back slightly. At the same time, the entire plow section turns upward and slides over the obstacle. Immediately upon passing the obstacle, the cutting edge moves back into clearing position and the return spring pushes the raised section back down against the street.



MUNICIPAL SNOWPLOWS

AT PLOW



ATE PLOW



EX EXPRESSWAY PLOW



RB DROTT SERIES PLOW



REVERSE-A-CAST



The Reversible AT plow features a spring adjustable trip moldboard to accommodate various edges and road contours.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
AT4210	10′	8′0″	42"	7ga	2150
AT4211	11′	9′0″	42"	7ga	2230
AT4212	12′	9′10″	42"	7ga	2310

Features: Available with flared ends and an overall height of 48 inches. Also available in 36 inch height.

The ATE - Torsion Spring Trip-Edge Plow features a spring adjustable trip moldboard to accommodate various edges and road contours.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
ATE3610	10′	8'0"	36"	10ga	1700
ATE3611	11′	9′0″	36"	10ga	1800
ATE3612	12′	9'10"	36″	10ga	1900

Features: Adjustable pitch moldboard, solid welded ribs, built-in deflector, dual revering cylinders

The Expressway Plow is a high speed, reversible trip moldboard snowplow. Dual discharge offers the efficiency of a one-way plow and the versatility of a reversible plow.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 35°	CUTTING WIDTH (ft,in) AT 35°	NOSE HEIGHT	DISCHARGE HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
EX1160	11′	9′0″	8'2"	38″	60"	10ga	2030
EX1270	12′	9′10″	8'11"	44"	70″	10ga	2360

(Trip moldboard with shear bars shown in image)

Designed to be closely mounted to the truck, this reversing plow has two adjustable coil springs and a smooth rolled moldboard for optimum casting.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 36°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
RB3711	11′	9′0″	37"	10ga	1575
RB3712	12′	9'10"	37″	10ga	1650
RB4211	11′	9′0″	42"	10ga	1700
RB4212	12′	9'10"	42"	10ga	1780

Features: Heavy-duty bottom reinforcement and A-frame design

When you need to change the shape of your plow to throw snow where you want to, Wausau's Revers-a-Cast plow gives you these options. Highly-adjustable, it's easy to change from right to left on the move.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 36°	HEIGHT	3070	WEIGHT (lbs)*
RAC11	11′	9'3"	33"-51"	3380	2870
RAC12	12′	10'2"	33"-51"	3/8" poly	3060
RAC14	14′	11′9″	33"-51"	2870	3380

Flexible poly moldboard changes shape and positions for maximum versatility without slowing operations

ROAD TOUGH



Road Tough is an all purpose plow for municipal and highway use. Built with a heavy-duty, reversible, trip moldboard this reversing plow gives you the performance you need, day in / day out.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 32°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
R3610	10′	8'2"	36″	3/16"	1440
R3611	11′	9′0″	36"	3/16"	1590
R4511	11′	9′0″	45″	3/16"	1670
R4512	12′	9'10"	45″	3/16"	1820
R4514	14	11′5″	45″	3/16"	2025
R4516	16	13′0′	45″	3/16″	2275

Features: Smooth rolled moldboard, 1/2" ribs, 4" x 6" reversing frame, 4" double-acting reverse cylinders

ROAD TOUGH ONE-WAY



SNOBARE



V-PLOW



WAVE ONE-WAY



This is a one-way version of our popular Road Tough reversing plow. Great for when you need to cast snow far away from the road surface.

MODEL	LENGTH CUTTING EDGE (ft)	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	WEIGHT (lbs)*
TB3050	10′11″	11'4"	8'11"	30"	50"	3/16"	1790
TB3256	11'7"	12'2"	8'8"	32"	56"	3/16"	1990

SnoBare is a rugged power reversing trip-edge plow design for medium duty trucks. Standard configuration consists of a poly moldboard, heavy-duty torsion springs and telescopic reversing cylinders.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in)	HEIGHT	WEIGHT (lbs)*
SB9	9′	7'9"	30"	820
SB10	10′	8'8"	30"	875
SB11	11′	9′6″	30"	930

Trip activation achieved through four or five torsion springs from 1/2" square wire

Designed for municipal and highway use when you need to open roads and need high-speed casting and snow removal.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DISCHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	WEIGHT (lbs)*
VHS3986	10′6″	8'6"	39"	70″	10g	1940
V5796	13'7"	9'6"	57″	90″	3/16"	2850
V5890	13′4″	9′0″	58″	88"	3/16"	2760
VX5896	13'7"	9'6"	58″	90"	3/16"	2900
VX5810	13'10"	10'0"	58″	92″	3/16"	3050

One-way, slotted trip snowplow designed for fast and efficient snow removal. Buffered design provides shock absorption when encountering road obstacles without dumping snow on cleared road.

MODEL	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	TRIP SPRINGS	WEIGHT (lbs)*
WW2452	13′1″	9′0″	24″	52″	3/16"	2	2560
WW3269	13'10"	9′0″	32″	69"	3/16"	2	2700

NOTE: all plow weights are approximate based on standard configurations excluding optional add-ons