

Municipal Equipment



OFTEN IMITATED - NEVER EQUALED - HomeSafe

HOMESAFE POLY SERIES





This is the most popular plow on the market for a reason. When it comes to a plow that can handle tough and varying terrains, this plow will get you home... safe.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
HSP3610	10′	8′	36"	3/8"	2100
HSP3611	11′	8' 9"	36"	3/8"	2180
HSP3612	12′	9'6"	36"	3/8"	2260
HSP4210	10′	8′	42"	3/8"	2260
HSP4211	11′	8′ 9″	42"		2340
HSP4212	12′	9′ 6″	42"		2420
HSP4214	14′	11′4″	42"	3/8"	2540
HSP4811	11"	8′ 9″	48"	3/8"	2500
HSP4812	12′	9′6″	48"	3/8"	2580

Choose between hydraulic, manual, worm gear reversing. Available options also include: single or dual mailbox cuts, rubber or poly snow deflectors, air foils, snow wheels

HOMESAFE POLY HOTWING SERIES



Choose the HotWing HomeSafe Plow for superior discharge and ability to lift and throw snow.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT AT CENTER	HEIGHT AT DISCHARGE	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
HSP4211HW	11′	8' 9"	42"	54 1/2"	3/8"	2440
HSP4212HW	12′	9'6"	42"	57"	3/8"	2520
HSP4811HW	11′	8′9″	48"	60"	3/8"	2600
HSP4812HW	12′	9'6"	48"	63"	3/8"	2680
HSP5611HW	11′	8′9″	56"	72"	3/8"	2820
HSP5612HW	12′	9'6"	56"	72"	3/8"	2900

Choose between hydraulic or manual reversing. Available options also include: rubber or poly snow deflectors, air foils, snow wheels

HOMESAFE STEEL SERIES





Wausau offers a steel moldboard version of the HomeSafe design.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
HSS3610	10′	8′	36"	3/16"	2205
HSS3611	11′	8' 9"	36"	3/16"	2285
HSS3612	12′	9′6″	36"	3/16"	2365
HSS4210	10′	8′	42"	3/16"	2365
HSS4211	11′	8′9″	42"	3/16"	2445
HSS4212	12′	9′6″	42"	3/16"	2525
HSS4214	14′	11′4″	42"	3/16"	2640

Choose between hydraulic or manual reversing. Available options also include: single or dual mailbox cuts, rubber or poly snow deflectors, air foils, snow wheels

*Note: all weights listed are an approximate minimum based on a standard unit

OFTEN IMITATED - NEVER EQUALED - HomeSafe

HOMESAFE ONE-WAY





When it comes time to throw and cast snow out of the way, Wausau's HomeSafe One-Way Plow is the answer. Our heavy-duty smooth rolled moldboard with solid welded ribs will stand up to years of hard use. The deep integral shield design is great for driver visibility and eliminating annoying over-spray. Wausau's trip mechanism consists of 3/4" square wire horizontal torsion springs.

MODEL	LENGTH CUTTING EDGE (ft)	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	TRIP SPRINGS	WEIGHT (lbs)*
HSS2656	11′	12′8"	9′0"	26"	56"	10ga	5 Torsion	2360
HSS2658	12′	13'8"	9'8"	26"	58"	10ga	6 Torsion	2460

Hydraulic reversing or fixed angle available. Options include: rubber or poly snow deflectors, air foils, snow wheels, sight markers, carbide cutting edges, curb quards etc.

THE PROOF IS IN THE DESIGN - FROM THE TRIP EDGE TO THE MOLDBOARD AND THE FRAME, WAUSAU'S HOMESAFE PLOW MEETS THE MOST DEMANDING NEEDS AND SAFETY REQUIREMENTS.



^{*}Note: all weights listed are a minimum based on a standard unit

MF Street Smart - MULTI-SECTION PLOW





The Street SmartTM plow is a multi-section, shock absorbing, reversible snowplow. Each section functions independently to enhance snow removal operation for all types of conditions. Designed for added safety to protect plow, hitch, truck, and operator. Adapts to all types of hitches.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	RETURN SPRINGS	WEIGHT (lbs)*
MF3.4	10'6"	8'11"	41"	10ga	4	2650
MF5.4	11′9″	10'0"	44"	10GA	4	2900

When the Street SmartTM plow hits an obstacle, the flexible shock rail absorbs the impact and springs back slightly. At the same time, the entire plow section turns upward and slides over the obstacle. Immediately upon passing the obstacle, the cutting edge moves back into clearing position and the return spring pushes the raised section back down against the street.



MUNICIPAL SNOWPLOWS

AT PLOW



The Reversible AT plow features a spring adjustable trip moldboard to accommodate various edges and road contours.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	HEIGHT MOLDBOARD THICKNESS (in)	
AT4210	10′	8'0"	42"	7ga	2150
AT4211	11′	9′0″	42"	7ga	2230
AT4212	12′	9'10"	42"	7ga	2310

Features: Available with flared ends and an overall height of 48 inches. Also available in 36 inch height.

ATE PLOW



The ATE - Torsion Spring Trip-Edge Plow features a spring adjustable trip moldboard to accommodate various edges and road contours.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 37°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
ATE3610	10′	8′0″	36"	10ga	1700
ATE3611	11′	9′0″	36"	10ga	1800
ATE3612	12'	9'10"	36"	10ga	1900

Features: Adjustable pitch moldboard, solid welded ribs, built-in deflector, dual revering cylinders

EX EXPRESSWAY PLOW



The Expressway Plow is a high speed, reversible trip moldboard snowplow. Dual discharge offers the efficiency of a one-way plow and the versatility of a reversible plow.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 35°	CUTTING WIDTH (ft,in) AT 42°	NOSE HEIGHT	DISCHARGE HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
EX1160	11′	9′0″	8'2"	38"	60"	10ga	2030
EX1270	12'	9'10"	8'11"	44"	70"	10ga	2360

(Trip moldboard with shear bars shown in image)

RB DROTT SERIES PLOW



Designed to be closely mounted to the truck, this reversing plow has two adjustable coil springs and a smooth rolled moldboard for optimum casting.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 36°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
RB3711	11′	9′0″	37"	10ga	1575
RB3712	12′	9'10"	37"	10ga	1650
RB4211	11′	9′0″	42"	10ga	1700
RB4212	12′	9′10″	42"	10ga	1780

Features: Heavy-duty bottom reinforcement and A-frame design

REVERSE-A-CAST



When you need to change the shape of your plow to throw snow where you want to, Wausau's Reverse-a-Cast plow gives you these options. Highly-adjustable, it's easy to change from right to left on the move.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 36°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
RAC11	11′	9'3"	33"-51"	3/8" poly	2870
RAC12	12'	10'2"	33"-51"	3/8" poly	3060
RAC14	14′	11′9″	33"-51"	3/8" poly	3380

Flexible poly moldboard changes shape and positions for maximum versatility without slowing operations.

ROAD TOUGH



Road Tough is an all purpose plow for municipal and highway use. Built with a heavy-duty, reversible, trip moldboard this reversing plow gives you the performance you need, day in / day out.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in) AT 35°	HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
R3610	R3610 10'		36"	3/16"	1440
R3611	11′	9′0″	36"	3/16"	1590
R4511	11′	9′0″	45"	3/16"	1670
R4512	12′	9'10"	45"	3/16"	1820
R4514	14	11′5″	45"	3/16"	2025
R4516	16	13'0'	45"	3/16"	2275

Features: Smooth rolled moldboard, 1/2" ribs, 4" x 6" reversing frame, 4" double-acting reverse cylinders

ROAD TOUGH ONE-WAY



This is a one-way version of our popular Road Tough reversing plow. Great for when you need to cast snow far away from the road surface.

MODEL	LENGTH CUTTING EDGE (ft)	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in) AT 35°	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	WEIGHT (lbs)*
TB3050	10′11"	11′4″	8'11"	30"	50"	3/16"	1790
TB3256	11′7″	12′2″	9′6″	32"	56"	3/16"	1990

SNOBARE



SnoBare is a rugged power reversing trip-edge plow design for medium duty trucks. Standard configuration consists of a poly moldboard, heavy-duty torsion springs and telescopic reversing cylinders.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in)	HEIGHT	WEIGHT (lbs)*
SB9	9′	7'9"	30"	820
SB10	10′	8'8"	30"	875
SB11	11′	9'6"	30"	930

Trip activation achieved through four or five torsion springs from 1/2" square wire

V-PLOW



Designed for municipal and highway use when you need to open roads and need high-speed casting and snow removal.

MODEL	LENGTH (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DISCHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	WEIGHT (lbs)*
VHS3986	10'6"	8'6"	39"	70"	10g	1940
V5796	13'7"	9'6"	57"	90"	3/16"	2850
V5890	13'4"	9′0″	58"	88"	3/16"	2760
VX5896	13'7"	9'6"	58"	90"	3/16"	2900
VX5810	13′10″	10′0″	58"	92"	3/16"	3050

WAVE ONE-WAY



One-way, slotted trip snowplow designed for fast and efficient snow removal. Buffered design provides shock absorption when encountering road obstacles without dumping snow on cleared road.

MODEL	LENGTH OVERALL (ft)	CUTTING WIDTH (ft,in)	NOSE HEIGHT (in)	DIS- CHARGE HEIGHT (in)	MOLDBOARD THICKNESS (ga)	TRIP SPRINGS	WEIGHT (lbs)*
WW2452	13′1″	9'0"	24"	52"	3/16"	2	2560
WW3269	13′10″	9'0"	32"	69"	3/16"	2	2700

NOTE: all plow weights are approximate based on standard configurations excluding optional add-ons

MUNICIPAL WINGS AND SCRAPERS

PATROL WING



Wausau's Patrol Wing is a full hydraulic lift available with a traditional post or a parallel lift group. Hydraulic teletube option for great visibility through passenger door window. Left, right and dual mount.

ı	MODEL	LENGTH (ft)	CUTTING EDGE LENGTH (ft)	NOSE HEIGHT	DISCHARGE HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
	PW8	8′	7'	26"	33"	3/16"	1745
	PW9	9'	8′	26"	34"	3/16"	1790
	PW10	10′	9'	26"	35"	3/16"	1835

Truck or loader mount wings are available. Polyethylene moldboard is also available.

SPACE PATROL WING



Extending the swath of a front plow, the Space Patrol Wing is designed for benching up to 36". Standard equipment includes an 8" C channel front post, trip moldboard and optional trip edge with parallel.

MODEL	LENGTH (ft)	CUTTING EDGE LENGTH (ft)	NOSE HEIGHT	DISCHARGE HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
SPW10	10′	9'	27"	34"	10ga	2370
SPW11	11′	10′	27"	35"	10ga	2440
SPW12	12'	11′	27"	36"	10ga	2510
SPW13	13′	12'	27"	37"	10ga	2580

LEVELING WING



Designed for rugged duty on tandem and 4-wheel drive truck chassis - our high benching wing helps you manage heavy snow accumulation. Flexibility to mount in left, right and dual configurations.

MODEL	LENGTH (ft)	CUTTING EDGE LENGTH (ft)	NOSE HEIGHT	DISCHARGE HEIGHT	MOLDBOARD THICKNESS (in)	WEIGHT (lbs)*
RERP10	10′	9′	27"	34"	3/16"	3500
RERP11	11′	10′	27"	35"	3/16"	3570
RERP12	12′	11′	27"	36"	3/16"	3640
RERP13	13′	12'	27"	37"	3/16"	3710s

PORK BELLY SCRAPER



The Pork Belly (PB) Underbody blade is built to perform and last through the harshest of conditions. Our rugged design includes a 1" moldboard and turntable, reversing cylinders and trip cushion springs.

MODEL	CUTTING WIDTH AT 0°	CUTTING WIDTH AT 15°	CUTTING WIDTH AT 35°	CUTTING WIDTH AT 45°	MOLDBOARD THICKNESS (ga)	MOLD- BOARD HEIGHT	REVERSE TABLE	WEIGHT (lbs)*
PB10	10′	9'7"	8'2"	7′1″	1"	17/20"	1"	2630
PB11	11′	10′7″	9′0″	7'9"	1"	17/20"	1"	2680
PB12	12'	11′7″	9'10"	8'6"	1"	17/20"	1"	2730

UNDERBODY GRADER




When you need versatility, Wausau's TG Underbody Scraper gives you 3 axes of rotation - reversing, up/down and oscillating side to side for following road contours. The operator can apply light, medium or heavy pressure while the accumulator provides built-in safety when hitting obstructions.

MODEL	CUTTING WIDTH AT 0°	CUTTING WIDTH AT 15°	CUTTING WIDTH AT 35°	MOLD- BOARD HEIGHT	DROP BELOW GRADE	HOIST, VERTICAL TRAVEL	PITCH VERTICAL TRAVEL	WEIGHT (lbs)*
TG8	8′	7'8"	6′7″	13/15"	4"	12"	8"	1920
TG10	10′	9'7"	9′1″	13/15"	4"	12"	8"	2000
TG12	12'	11′7″	9′1″	13/15"	4"	12"	8"	2080



OFTEN IMITATED - NEVER EQUALED



FULL LINE OF SNOW & ICE EQUIPMENT FOR MUNICIPALITIES AND AIRPORTS

- SNOW BLOWERS
- SNOW PLOWS
- SNOW WINGS
- HITCHES
- SCRAPERS
- SPREADERS
- SEVERE DUTY TRUCKS
- TUNNEL WASHING MACHINES



Awarded Contract

Contract # 080818-WAS

262.784.6066

sales@wausauequipment.com

wausauequipment.com