



epoke[®]
GROUP

THE ITM SERIES

- the simple towed spreader in three sizes



- the safe way!

The ITM Series

ITM spreaders are smaller salt and sand spreaders that connect to the implement carrier's towing hook.

ITM spreaders are therefore ideal for fast work on bicycle paths, footpaths, car parks and similar areas. With a low deadweight and a low centre of gravity, ITM spreaders are easy to manoeuvre.

ITM spreaders are driven by the spreader's road wheel, and the spreading amount is regulated via a handle, which is connected to the spring base adjustment.

The spreaders are speed-compensated and thus always apply the selected spreading amount regardless of changes in speed.

The simple and robust design using well-known Epoke quality ensures excellent reliability and low maintenance costs.

Standard equipment

- Rubber base
- Spring base
- Spring base adjustment
- Distributor roller
- Transmission
- Wheels

Optional extras

- Agitator
- Drawbar with eye or ball coupling
- Three-point hitch
- Fitting for forklift truck
- Lights
- Electronic remote control
- Tarpaulin

Technical data and dimensions

	ITM 35	ITM 45	ITM 60
Approximate volume of hopper, l	350	450	600
Min. spreading width, mm	780	1000	1146
Track width, mm	1020	1290	1730
Total width, mm	1150	1435	1885
Deadweight, kg	145	192	220



The spreading amount is set using the handle, which controls the spring base adjustment.



The electronic remote control is available as an optional extra.



Built-in support feet means simple unloading and towing.